



SVJETLO  
IZ BETONA

ELTOR  
IDEASINLIGHTING

Beton  
učko

PLAN10  
LANDSCAPE ARCHITECTURE


Holcim

# ASTON


## VISEĆA SVJETILJKA SUSPENDED LAMP



Bijela/White  
(W)



Siva/Gray  
(G)



Smeđa/Brown  
(S)

W	K	V	ØxH	kg
1xGU10	3K/4K	230V	115x150	1,2
1xGU10	3K/4K	230V	168x260	1,6

#### NAMJENA / USAGE



**Kućište:** beton glatke površinske obrade

**Standardna boja:** bijela, siva, smeđa

**Napajanje:** 230V/50Hz

**Električne komponente:** ugrađene u kućište

**Izvor svjetla:** GU 10 žarulje

**Montaža:** vješanjem na napojni kabel, max.L=1500 mm

**Spajanje:** skidanjem ukrasne rozete dostupne su priključne stezaljke i ostale električne komponente

**Housing:** smooth surface concrete

**Standard color:** white, gray, brown

**Power:** 230V/50Hz

**Supply unit:** built in the housing

**Light source:** GU10 bulbs

**Mounting:** hanging on power supply cable, max.L=1500 mm

**Connecting:** through removing the decorative box, connection clamps and all other electronic components are available

Betonska visilica glatke površinske obrade dolazi u bijeloj, sivoj i smeđoj boji. Površina betona impregnirana je transparentnom impregnacijom koja olakšava održavanje, te ju čini otpornom na prljavštinu, mrlje, upijanje vode i ulja. Impregnacija je bezbojna i u potpunosti neprimjetna, te s vremenom ne mijenja boju. Visilice su dostupne u dvije veličine v/š/d=150/115/25 mm i v/š/d=260/168/32,5 mm. Ciljana težina betonskog dijela visilice iznosi otprilike 1600 g. Unutar visilice ugrađena je cijev promjera 10 mm kroz koju se provlači kabel s glom i žaruljom.

Concrete suspended luminaire, with smooth surface finishing, comes in white, gray and brown color. Surface is impregnated with transparent impregnation that makes maintenance easier and surface resistant to dirt, marks, oil and water absorption. Impregnation is colorless, invisible and doesn't turn yellow over time. Concrete luminaire comes in two sizes: h/w/l = 150/115/25 mm and h/w/l = 260/168/32,5 mm. Targeted weight of the concrete part is approximately 1600 g. Inside the luminaire is a built in tube (with diameter of 10 mm), that houses a cable with a socket and a bulb.



**Kućiče:** od impregniranog betona

**Standardna boja:** siva

**Napajanje:** 230V/50Hz

**Električne komponente:** ugrađene u kućište

**Izvor svjetla:** LED nove generacije, MacAdam 3, CRI>80; LED min 60.000h L80F50 na Tp=65°C, EEL A++

**Difuzor:** zaštitni transparentni polikarbonat

**Montaža:** pomoću anker vijaka i temeljne toploćinčane metalne ploče

**Spajanje:** na priključni kabel

Housing: from impregnated concrete

Standard color: gray

Power: 230V/50Hz

Supply unit: built in the housing

Diffuser: from protective transparent polycarbonate

Light source: new generation LED, MacAdam 3, CRI>80; LED min 60.000h L80F50 on Tp=65°C; EEL A++

Mounting: using log bolts and galvanized metal sheet base

Connecting: to connecting cable

W	K	V	AxBxH	kg
3W	3K/4K	230V	300x180x500	34
6W	3K/4K	230V	300x180x500	34

# B-TONE

BETONSKI  
RASVJETNI

LED STUP

CONCRETE

LED

LIGHT POLE

Betonski antivandalski stupić debljine 18 cm, visine 50 cm i širine 30 cm, težine cca 34 kg izrađen od betona tlačne čvrstoće C30/37 razreda izloženosti XC4, XS1, XD2, XA1, XF1. Rubovi betonskog stupića rasvjete skošeni su pod kutem od 45°, katete 1x1 cm. Obrada betonske površine stupića rasvjete može biti glatka i prana u boji po izboru projektanta. Površina betonskog stupića impregnirana je transparentnom impregnacijom koja je otporna na prljavštinu i mrlje, upijanje vode i ulja. Na impregniranoj površini ne stvara se vidljivi film, bezbojna je i nakon sušenja ne žuti. U stupić prilikom izrade ugrađuje se kutija za elektroinstalacije. Stupić se postavlja na izvedene AB temelje i povezuje anker vijcima.

Concrete antivandal pole in length 18cm, height 50cm and width 30cm, weight approx 34kg made from concrete in compressive strength C30/37 class XC4, XS1, XD2, XA1, XF1. Edges are slanted at 45°, 1x1cm cathetus. Surface treatment can be smooth and washed in color by choice. Area of pole is impregnated by transparent impregnation which is resistant to dirt, water and oil absorption. At surface level no visible trace is left, colorless and won't turn yellow. With box for electrical installations. The pole is mounted at concrete foundation with log bolts.

NAMJENA / USAGE





GRADIMO  
S VAMA I ZA VAS!



**BETON LUČKO d.o.o.**

10250 Lučko / Puškarićeva 1b

tel: +385 (1) 65 99 700

fax: +385 (1) 65 30 070

[info@betonlucko.hr](mailto:info@betonlucko.hr)

[www.betonlucko.hr](http://www.betonlucko.hr)



**Holcim (Hrvatska) d.o.o.**

Koromačno 7b / 52222 Koromačno

[holcim-hrvatska@lafargeholcim.com](mailto:holcim-hrvatska@lafargeholcim.com)

[www.facebook.com/HolcimHrvatska](https://www.facebook.com/HolcimHrvatska)

[www.holcim.hr](http://www.holcim.hr)